





MRS		ORFS MALE <i>MASCHIO ORFS</i>										AG ORFS	
TIEFFE Part.N.	Hose Size			ORFS Connection Size		Dimensions (mm)					Maximum W.P.		
	DN	Inch	Dash	F	Dash	H	L	S	O-RING	bar	PSI		
													
CH1212MRS	19	3/4"	-12	1 3/16"-12	-12	34	95	32		18,77x1,78	420	6000	
CH1616MRS	25	1"	-16	1 7/16"-12	-16	37	110	41		23,52x1,78	415	6000	
CH2020MRS	31,5	1 1/4"	-20	1 11/16"-12	-20	40	128	46		29,87x1,78	345	5000	
CH2424MRS	38	1 1/2"	-24	2"-12	-24	43	136	55		37,82x1,78	250	4200	

FRS		ORFS FEMALE - SLIP-ON NUT <i>FEMMINA ORFS - DADO LIBERO</i>										DK ORFS	
TIEFFE Part.N.	Hose Size			ORFS Connection Size		Dimensions (mm)					Maximum W.P.		
	DN	Inch	Dash	F	Dash	H	L	S			bar	PSI	
													
CH1212FRS	19	3/4"	-12	1 3/16"-12	-12	35	97	36			420	6000	
CH1616FRS	25	1"	-16	1 7/16"-12	-16	37	110	41			415	6000	
CH2020FRS	31,5	1 1/4"	-20	1 11/16"-12	-20	38	126	50			345	5000	
CH2424FRS	38	1 1/2"	-24	2"-12	-24	39	132	60			290	4200	

FRS45		ORFS FEMALE - 45° ELBOW - SLIP-ON NUT <i>FEMMINA ORFS - CURVA A 45° - DADO LIBERO</i>										DK ORFS 45	
TIEFFE Part.N.	Hose Size			ORFS Connection Size		Dimensions (mm)					Maximum W.P.		
	DN	Inch	Dash	F	Dash	H	L	K	S		bar	PSI	
													
CH1212FRS45B	19	3/4"	-12	1 3/16"-12	-12	63	125	26	36		420	6000	
CH1616FRS45B	25	1"	-16	1 7/16"-12	-16	78	151	31	41		415	6000	
CH2020FRS45B	31,5	1 1/4"	-20	1 11/16"-12	-20	96	184	36	50		345	5000	
CH2424FRS45B	38	1 1/2"	-24	2"-12	-24	113	207	42	60		290	4200	

FRS90		ORFS FEMALE - 90° ELBOW - SLIP-ON NUT <i>FEMMINA ORFS - CURVA A 90° - DADO LIBERO</i>										DK ORFS 90	
TIEFFE Part.N.	Hose Size			ORFS Connection Size		Dimensions (mm)					Maximum W.P.		
	DN	Inch	Dash	F	Dash	H	L	K	S		bar	PSI	
													
CH1212FRS90B	19	3/4"	-12	1 3/16"-12	-12	56	118	55	36		420	6000	
CH1616FRS90B	25	1"	-16	1 7/16"-12	-16	71	144	67	41		415	6000	
CH2020FRS90B	31,5	1 1/4"	-20	1 11/16"-12	-20	90	177	81	50		345	5000	
CH2424FRS90B	38	1 1/2"	-24	2"-12	-24	107	201	95	60		290	4200	