


**YP90**

**"SUPERCAT" FLANGE - 90° ELBOW**  
*FLANGIA "SUPERCAT" - CURVA A 90°*

**SFS90**  
*SUPERCAT*




Part.N.	Hose Size			Flange Size Connection		Dimensions (mm)					Maximum W.P.	
	DN	Inch	Dash	Inch	Dash	H	L	K	A		bar	PSI
<b>CS1212YP90</b>	19	3/4"	-12	3/4"	-12	55	106	64	41,3		420	6000
<b>CS1216YP90</b>	19	3/4"	-12	1"	-16	55	106	64	47,6		420	6000
<b>CS1616YP90</b>	25	1"	-16	1"	-16	71	128	73	47,6		415	6000
<b>CS1620YP90</b>	25	1"	-16	1 1/4"	-20	71	128	73	54		415	6000
<b>CS2020YP90</b>	31,5	1 1/4"	-20	1 1/4"	-20	87	154	77	54		415	6000
<b>CS2024YP90</b>	31,5	1 1/4"	-20	1 1/2"	-24	87	154	78	63,5		415	6000
<b>CS2424YP90</b>	38	1 1/2"	-24	1 1/2"	-24	105	188	90	63,5		415	6000
<b>CS2432YP90</b>	38	1 1/2"	-24	2"	-32	105	188	94	79,4		415	6000
<b>CS3232YP90</b>	51	2"	-32	2"	-32	140	237	125	79,4		345	5000

**YP90**

*LONG DROP*

**"SUPERCAT" FLANGE - 90° ELBOW - LONG DROP**  
*FLANGIA "SUPERCAT" - CURVA A 90° - LUNGA*

**SFS90**  
*SUPERCAT LONG DROP*



Part.N.	Hose Size			Flange Size Connection		Dimensions (mm)					Maximum W.P.	
	DN	Inch	Dash	Inch	Dash	H	L	K	A		bar	PSI
<b>CS1212YP90-K129</b>	19	3/4"	-12	3/4"	-12	55	106	129	41,3		420	6000
<b>CS1616YP90-K132</b>	25	1"	-16	1"	-16	71	128	132	47,6		415	6000
<b>CS1616YP90-K150</b>	25	1"	-16	1"	-16	71	128	150	47,6		415	6000
<b>CS2020YP90-K150</b>	31,5	1 1/4"	-20	1 1/4"	-20	87	154	150	54		415	6000
<b>CS2024YP90-K135</b>	31,5	1 1/4"	-20	1 1/2"	-24	87	154	135	63,5		415	6000
<b>CS2424YP90-K106</b>	38	1 1/2"	24	1 1/2"	-24	105	188	106	63,5		415	6000

