


FOS-S45

METRIC FEMALE 24° O'RING CONE - 45° ELBOW - HEAVY DUTY - SLIP-ON NUT
FEMMINA METRICA OGIVA 24° O'RING - CURVA A 45° - SERIE PESANTE - DADO LIBERO

DKOS45




Part.N.	Hose Size			METRIC 24° Connection		Dimensions (mm)					Maximum W.P.	
	DN	Inch	Dash	F	Pipe	H	L	K	S	O-RING	bar	PSI
CS12FOS20S45	19	3/4"	-12	M30x2	20S	65	116	27	36	16,3x2,4	420	6000
CS12FOS25S45	19	3/4"	-12	M36x2	25S	66	117	28	46	20,3x2,4	420	6000
CS16FOS25S45	25	1"	-16	M36x2	25S	83	140	34	46	22x2	380	5500
CS16FOS30S45	25	1"	-16	M42x2	30S	82	138	32	50	25,3x2,4	380	5500
CS20FOS30S45	31,5	1 1/4"	-20	M42x2	30S	100	166	40	50	25,3x2,4	325	4700
CS20FOS38S45	31,5	1 1/4"	-20	M52x2	38S	97	164	38	60	33,3x2,4	325	4700
CS24FOS38S45	38	1 1/2"	-24	M52x2	38S	121	203	48	60	33,3x2,4	290	4200

FOS-S90

METRIC FEMALE 24° O'RING CONE - 90° ELBOW - HEAVY DUTY - SLIP-ON NUT
FEMMINA METRICA OGIVA 24° O'RING - CURVA A 90° - SERIE PESANTE - DADO LIBERO

DKOS90



Part.N.	Hose Size			METRIC 24° Connection		Dimensions (mm)					Maximum W.P.	
	DN	Inch	Dash	F	Pipe	H	L	K	S	O-RING	bar	PSI
CS12FOS20S90	19	3/4"	-12	M30x2	20S	55	106	55	36	16,3x2,4	420	6000
CS12FOS25S90	19	3/4"	-12	M36x2	25S	55	106	55	46	20,3x2,4	420	6000
CS16FOS25S90	25	1"	-16	M36x2	25S	71	128	69	46	22x2	380	5500
CS16FOS30S90	25	1"	-16	M42x2	30S	71	128	67	50	25,3x2,4	380	5500
CS20FOS30S90	31,5	1 1/4"	-20	M42x2	30S	87	154	83	50	25,3x2,4	325	4700
CS20FOS38S90	31,5	1 1/4"	-20	M52x2	38S	87	154	80	60	33,3x2,4	325	4700
CS24FOS38S90	38	1 1/2"	-24	M52x2	38S	105	188	100	60	33,3x2,4	290	4200